



12 to 320 CFM Shaded Pole Blowers



No. 2C782, 4C759



No. 4C760 & 4C763



No. 4C012



No. 4C441



No. 2C914 & 4C440



No. 4C004, 4C006 & 4C446



No. 4C443



No. 2C067



No. 2C647 & 2C646



No. 2C915 & 4C442



No. 4C015 & 2C069



No. 1C982 & 2C916



No. 4C754



No. 4C447 & 4C869

0.0" SP	0.1" SP	CFM @ RPM Shown		0.4" SP	0.5" SP	Volts	Hz	Thermal Protection	RPM	0.0" SP	Amps	Stock No.	Each	Lots 3	Shpg. Wt.
		0.2" SP	0.3" SP												
12	9	—	—	—	—	115	60	Impedance	3300	0.35		4C759	\$29.55	\$27.98	1.8
15	13	4	—	—	—	115	60/50	Impedance	3160	0.35/0.30		2C782	40.60	38.45	2.3
31	28	25	20	7	—	115	60	Impedance	3010	0.45		4C760	36.35	34.36	2.3
50	46	43	37	29	15	115	60	Impedance	2840	0.53		4C761	37.20	35.22	2.8
54	48	43	36	25	17	115	60/50	Auto	3340	0.91/0.83		4C012✓	45.35	42.92	3.2
60	57	54	49	39	23	115	60/50	Auto	3030	0.55/0.49		4C441✓	44.25	41.91	3.4
60	57	54	49	39	23	115	60/50	Auto	3030	0.49/0.42		4C440✓	47.80	45.20	3.6
60	57	54	49	39	23	230	60/50	Auto	3020	0.28/0.23		2C914✓	46.80	44.38	3.6
72	65	58	49	40	19	115	60	Impedance	2930	0.55		4C762	40.75	38.60	4.0
76	70	63	56	45	8	115	60/50	Auto	2880	0.60/0.62		4C004✓	50.35	47.67	4.0
98	92	86	77	69	54	115	60	Auto	2870	1.55		4C763✓	48.80	46.22	4.0
70	65	60	55	50	45	115	60/50	Auto	2870	0.95/0.74		4C443✓	54.35	51.51	4.0
108	94	79	61	25	—	115	60/50	Auto	1530	0.64/0.58		2C067✓	64.25	60.95	4.7
134	126	117	107	96	79	115	60/50	Auto	1500	0.74/0.78		2C647✓	48.35	48.30	4.5
140	136	131	125	119	110	115	60/50	Auto	3020	1.16/1.02		4C442✓	63.10	59.74	5.5
140	136	131	125	119	110	230	60/50	Auto	3020	0.58/0.54		2C915✓	67.95	64.41	5.4
148	141	135	129	121	114	115	60/50	Auto	3160	1.54/1.37		4C446✓	57.95	54.93	5.6
157	145	134	116	103	72	115	60/50	Auto	3180	0.99/0.88		4C015✓	74.50	70.57	5.2
160	151	141	125	93	16	115	60/50	Auto	1570	1.23/1.00		1C982✓	63.85	60.52	5.6
160	151	141	125	93	16	230	60/50	Auto	1610	0.50/0.50		2C916✓	71.60	67.84	6.2
176	170	165	159	153	148	12VDC	—	None	1875	5.10		2C646✓	44.95	44.90	4.2
200	196	191	189	182	176	115	60/50	Auto	1400	2.10/2.10		4C754✓	91.80	87.11	8.2
265	250	232	212	184	135	115	60/50	Auto	1610	1.95/1.86		4C447✓	67.70	64.15	8.6
265	250	232	212	184	135	230	60/50	Auto	1610	0.98/0.93		4C869✓	77.25	73.14	8.1
320	305	284	252	195	50	115	60/50	Auto	1320	1.32/1.27		2C069✓	104.25	98.90	9.6
0.0" SP	0.5" SP	0.7" SP	0.9" SP	1.0" SP	1.2" SP	Volts	Hz	Thermal Protection	RPM	0.5" SP	Amps	Stock No.	Each	Lots 3	Shpg. Wt.
#	118	107	95	82	42	115	60/50	Auto	2288		1.54/1.40	4C006✓	\$59.00	\$55.92	5.1

CFM values shown are representative of catalog specifications within a tolerance of ±15%.

CONTINUED